

# 1972-73 MERC MODELS

Motor Model	Clockwise RH Rotation	Propeller				Approx. Gross Load Lbs.	Approx. Boat Length	Transom Height		Speed Range MPH
		Dia.	Pitch	No. Bl.	Material			Std. Length	Long Shaft	
Merc 40 RPM Range 4500-5500	A-48-63494A1	8 1/4"	6	2	Alum.	All Purpose	All Purpose	15"	20"	All Purpose
Merc 75 RPM Range 4500-5500	A-48-47922A1	9"	9	2	Alum.	Up to 450	8-13'	15"	20"	15-20
	A-48-47670A1	8 3/4"	7	3	Alum.	All Purpose	All Purpose	15"	20"	3-16
Merc 110 RPM Range 4500-5500	A-48-47924A1	9"	10"	2	Bronze	Up to 700	11-14'	15"	20"	15-26
	A-48-47926A1	9"	10"	2	Alum.	Up to 700	11-14'	15"	20"	15-26
	A-48-47922A1	9"	9"	2	Alum.	400-700	12-15'	15"	20"	15-20
	A-48-47670A1	8 3/4"	7"	3	Alum.	Aux. Power or Work Boat		15"	20"	1-15
Merc 200 RPM Range 4800-5500	A-48-49446A4	9-7/8"	11"	2	Bronze	Up to 750	Up to 13'	15"	20"	24-35
	A-48-34402A1	9-7/8"	11"	2	Bronze	Up to 1000	12-15'	15"	20"	22-33
	A-48-33480A1	9-7/8"	11"	2	Alum.	Up to 1000	12-15'	15"	20"	22-33
	A-48-33482A1	9-7/8"	9"	3	Alum.	850-1600	15' Plus	15"	20"	13-24
	A-48-37316A1	9-7/8"	7"	3	Alum.	Aux. Power or Work Boat		15"	20"	1-14
Merc 402 RPM Range 4800-5300	A-48-63452A1	10 3/4"	17"	2	Bronze	Up to 900	12-14'	15 1/2"	20"	32-38
	A-48-56230A1	10 3/4"	17"	3	Alum.	Up to 900	12-14'	15 1/2"	20"	32-38
	A-48-63454A1	10 3/4"	15"	2	Bronze	700-1100	12-15'	15 1/2"	20"	28-34
	A-48-56232A1	10 3/4"	15"	3	Alum.	700-1100	12-15'	15 1/2"	20"	28-34
	A-48-63456A1	11"	13"	2	Bronze	800-1200	14-16'	15 1/2"	20"	24-30
	A-48-56236A1	10 3/4"	13"	3	Alum.	800-1200	14-16'	15 1/2"	20"	24-30
	A-48-63458A1	11"	12"	2	Bronze	1200-1700	15-17'	15 1/2"	20"	22-28
	A-48-56240A1	10 3/4"	12"	3	Alum.	1200-1700	15-17'	15 1/2"	20"	22-28
	A-48-63460A1	11"	11"	2	Bronze	1500-1800	16-19'	15 1/2"	20"	19-26
	A-48-56244A1	10 3/4"	11"	3	Alum.	1500-1800	16-19'	15 1/2"	20"	19-26
	A-48-56246A1	10 3/4"	10"	3	Alum.	1600-2000	18-22'	15 1/2"	20"	15-23
	A-48-63464A1	10 3/4"	9"	3	Bronze	Aux. Power or Work Boat		15 1/2"	20"	1-16
	A-48-56248A1	10 3/4"	9"	3	Alum.	Aux. Power or Work Boat		15 1/2"	20"	1-16
Merc 500 RPM Range 4800-5500	A-48-56228A1	10 3/4"	19"	3	Alum.	Up to 1000	Up to 15'	15 1/2"	20"	37-44
	A-48-63452A1	10 3/4"	17"	2	Bronze	900-1200	14-16'	15 1/2"	20"	32-39
	A-48-56230A1	10 3/4"	17"	3	Alum.	900-1200	14-16'	15 1/2"	20"	32-39
	A-48-63454A1	10 3/4"	15"	2	Bronze	1000-1700	14-16'	15 1/2"	20"	28-35
	A-48-56232A1	10 3/4"	15"	3	Alum.	1000-1700	14-16'	15 1/2"	20"	28-35
	A-48-63456A1	11"	13"	2	Bronze	1200-2000	15-17'	15 1/2"	20"	24-32
	A-48-56236A1	10 3/4"	13"	3	Alum.	1200-2000	15-17'	15 1/2"	20"	24-32
	A-48-63458A1	11"	12"	2	Bronze	1400-2100	15-17'	15 1/2"	20"	22-31
	A-48-56240A1	10 3/4"	12"	3	Alum.	1400-2100	15-17'	15 1/2"	20"	22-31
	A-48-63460A1	11"	11"	2	Bronze	1600-2200	16-18'	15 1/2"	20"	19-30
	A-48-56244A1	10 3/4"	11"	3	Alum.	1600-2200	16-18'	15 1/2"	20"	19-30
	A-48-56246A1	10 3/4"	10"	3	Alum.	1800-2500	17-20'	15 1/2"	20"	15-26
	A-48-63464A1	10 3/4"	9"	3	Bronze	2400-Plus	20' Plus	15 1/2"	20"	1-16
A-48-56248A1	10 3/4"	9"	3	Alum.	2400-Plus	20' Plus	15 1/2"	20"	1-16	
Merc 650 RPM Range 4800-5300	A-48-64724A1	10 3/4"	17"	3	Alum.	Up to 750	Up to 14'	15 1/2"	20"	43-50
	A-48-64726A1	10 3/4"	17"	3	Bronze	Up to 750	Up to 14'	15 1/2"	20"	43-50
	A-48-61824A1	10 3/4"	16"	3	Alum.	Up to 850	12-14'	15 1/2"	20"	41-46
	A-48-63538A1	10 3/4"	16"	3	Bronze	Up to 850	12-14'	15 1/2"	20"	41-46
	A-48-61822A1	11"	15"	3	Alum.	Up to 950	13-15'	15 1/2"	20"	38-43
	A-48-63540A1	11"	15"	3	Bronze	Up to 950	13-15'	15 1/2"	20"	38-43
A-48-61820A1	11 1/4"	14"	3	Alum.	700-1300	14-16'	15 1/2"	20"	35-40	